

UZP Enzymatic Treatment

Premium industrial strength universal enzyme product, trillions not billions of beneficial bacteria, enzymes & nutrients per pound, super concentrated formula is multiple times stronger than competing products. The gold standard of enzymatic treatments look for the gold bag.

UZP Enzymatic Treatment for Floor & Wall Cleanup – Oil & Grease Removal

Usage Rates

For lightly soiled floors or walls: Mix 230 grams (8.11 oz.) of product in 16 liters (4.23 gallons) of warm water to treat 90 square meters (295.3 sq. ft.) of floor or wall area. If area is smaller use 20 grams (.71 oz.) of product per one liter (34 oz.) of water to treat every 7.8 square meters (25.7 sq. ft.) of floor or wall area.

For heavier soiled floors or walls: Mix 455 grams (16.05 oz.) of product in 16 liters (4.23 gallons) of warm water to treat 90 square meters (295.3 sq. ft.) of floor area. If area is smaller use 30 grams (1.1 oz.) of product per one liter (34 oz.) of water to treat every 7.8 square meters (25.7 sq. ft.) of floor or wall area. If more than one application is needed use the same ratios.

Application Instructions

1. Power Floor Scrubber Application
 - Using stiff bristle brushes – Pour product and water solution into the power scrubber reservoir tank.
 - Turn off vacuum and raise squeegee for this application.
 - Apply product solution evenly over the desired area, using the power scrubber
2. Hand Application
 - Pre-mix product and water solution in a separate pail and pour into a hand pump sprayer. For walls use a hand sprayer and mix product and water by agitating well.
 - Wet the area well with the product solution and agitate the sprayer to ensure proper mixing and eliminate settling.
 - Brush in with stiff bristle brush (street broom) for floors and hand brush for walls.
3. Allow solution to remain on the surface (floor or wall) for 30 minutes to an hour; reapplying as needed to ensure surface does not dry out. Every fifteen (15) minutes agitate the mixture on the floor surface with either the power floor scrubber or a stiff bristle brush and wall surfaces with a hand brush. Area should be kept wet during the entire treatment time using the product and water mixture. **Do not let area dry out.**

4. After one (1) hour, pick up solution on floor using the power floor scrubber with vacuum on, or a wet/dry vacuum, or rinse off with a water hose. For walls rinse off with a water spray bottle or similar.
5. It may be necessary to reapply product mixture a second time the next day for heavily soiled floors.
6. Let the floor air-dry.
7. After the floor is dry, mop with clear water or a water-soluble degreaser and water mix. For walls wipe off with damp cloth.

Cautions

- Store product in a cool, dry location. Do not open until ready to use.
- Do not mix more product than will be used in a 4 hour period.
- Mix product with warm, **NOT HOT**, water.
- The temperature of the treatment area has to be above 10°C (50F). Temperatures above 18.5°C (65.3F) are best.

Avoid using bleach or other chemicals that can kill the bacteria and enzymes. Always use warm water to mix the product before applying it.